
HP Super Heavyweight Plus Matte Paper





The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



- With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, Original HP 83 UV inks, or Original HP 70 Photo Inks on the HP Designjet Z5200 Postscript Printer and the HP Designjet Z2100 Photo Printer series. Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see globalBMG.com/hp/t/printpermanence.
- With Original HP 771 Vivid Photo Inks, or Original HP 91 or 70 Photo Inks. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.
- With Original HP 771 Vivid Photo Inks or Original HP 91 Photo Inks. Water resistance testing byHP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see globalBMG.com/hp/t/printpermanence.

Produce professional full-color graphics

See highly saturated images that lie flat, smooth

When the job requires professional full-color graphics and photo-realistic images this heavy, matte-finish paper—with a barrier layer under a thick top coating that enables ripple-free prints—delivers excellent highlights and rich shadow details.

Streamline your workflow

Move quickly and smoothly through post-print processing. Instant-dry, smear-resistant prints—even with high ink densities—enable immediate handling and lamination. Excellent film laminate compatibility helps you keep peak productivity.

Create durable prints for a versatile set of jobs

Produce a wide array of graphics-display applications and print with both Original HP dye-and pigment-based inks. Deliver prints with over 1 year, unlaminated indoor inwindow¹ display permanence, over 200 years indoor, away from direct sun.²

Target customers	Applications	Benefits	
Print service providers	Tradeshow and event displays	Highly-saturated, photo-realistic images	
Large retailers	Posters and presentations	Bright white, smooth coating for vivid color contrast	
Graphic designers	POP and retail displays	Flat, smooth prints even under high ink densities	
Ad agencies	Geographic Information Systems (GIS)	Excellent film laminate compatibility	
Repro houses	Architecture (AEC)	Instant-dry, smear-resistant prints	
Geographic Information Systems (GIS) professionals	Engineering (CAD)	Prints are water-resistant, unlaminated ³	
Architects		1+ years unlaminated in-window,¹ 200+ years indoor display permanence²	
		Compatible with both Original HP dye- and pigment-based inks	
		inks	

Technical specifications



HP Super Heavyweight Plus Matte Paper

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit **globalBMG.com/hp/**.

210 g/m² per ISO 53	210 g/m² per ISO 536 Test Method, (55 lbs)				
264 microns /10.4 m	264 microns /10.4 mil per ISO 534 Test Method				
98% per TAPPI T-42!	98% per TAPPI T-425 Test Method				
91% per TAPPI T-452	91% per TAPPI T-452 Test Method				
130 per CIE Ganz 82	130 per CIE Ganz 82 Test Method				
Matte	Matte				
15 to 35° C / 59 to 95	15 to 35° C / 59 to 95° F				
20 to 80% RH	20 to 80% RH				
with Original HP 91 F	1+ years unlaminated, 2+ years laminated with Original HP 771 Vivid Photo Inks; 1+ years unlaminated, 3+ years laminated with Original HP 91 Photo Inks; 1+ years unlaminated with Original HP 83 UV inks; 1+ years unlaminated or laminated with Original HP 70 Photo Inks on the HP Designjet Z5200 Postscript Printer and the HP Designjet Z2100 Photo Printer series				
	200+ years away from direct sun with Original HP 771 Vivid Photo Inks, or Original HP 91 or 70 Photo Inks; 100+ years away from direct sun with Original HP 83 UV inks ⁵				
Water resistant with	Water resistant with Original HP 771 Vivid Photo Inks or Original HP 91 Photo Inks ⁶				
Instant dry (at 23° C,	Instant dry (at 23° C, 50% RH)				
Yes, compatible with	Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates				
1 year, unopened in	1 year, unopened in original packaging				
0 to 40° C / 32 to 104	0 to 40° C / 32 to 104° F				
5 to 95% RH	5 to 95% RH				
Recyclable through o	Recyclable through commonly available recycling programs				
Product of Switzerla	Product of Switzerland				
Product numbers	Rollsizes	UPC codes	Region		
Q6626B	610 mm x 30,5 m (24 in x 100 ft)	848412013566	Worldwide		
Q6627B	914 mm x 30,5 m (36 in x 100 ft)	848412013573	Worldwide		
Q6628B	1067 mm x 30,5 m (42 in x 100 ft)	848412013580	Worldwide		
Q6630B	1524 mm x 30,5 m (60 in x 100 ft)	848412013597	Worldwide		
j ,	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see globalBMG.com/hp/MediaWarranties .				
	264 microns /10.4 m 98% per TAPPI T-42: 91% per TAPPI T-45: 130 per CIE Ganz 82 Matte 15 to 35° C / 59 to 95 20 to 80% RH 1+ years unlaminate with Original HP 91 FOriginal HP 70 Photo 200+ years away from direct sur Water resistant with Instant dry (at 23° C, Yes, compatible with 1 year, unopened in 0 to 40° C / 32 to 104 5 to 95% RH Recyclable through resident of Switzerla Product numbers Q6626B Q6627B Q6628B Q6630B HP large format p	264 microns /10.4 mil per ISO 534 Test Method 98% per TAPPI T-425 Test Method 91% per TAPPI T-452 Test Method 130 per CIE Ganz 82 Test Method Matte 15 to 35° C / 59 to 95° F 20 to 80% RH 1+ years unlaminated, 2+ years laminated with Original HP 7 with Original HP 91 Photo Inks; 1+ years unlaminated with Original HP 70 Photo Inks on the HP Designjet Z5200 Postsor 200+ years away from direct sun with Original HP 771 Vivid F away from direct sun with Original HP 83 UV inks ⁵ Water resistant with Original HP 771 Vivid Photo Inks or Original Instant dry (at 23° C, 50% RH) Yes, compatible with thermal, heat assist, and pressure-sen 1 year, unopened in original packaging 0 to 40° C / 32 to 104° F 5 to 95% RH Recyclable through commonly available recycling programs Product of Switzerland Product numbers Roll sizes Q6626B 610 mm x 30,5 m (24 in x 100 ft) Q6627B 914 mm x 30,5 m (36 in x 100 ft) Q6628B 1067 mm x 30,5 m (42 in x 100 ft) Q6630B 1524 mm x 30,5 m (60 in x 100 ft) HP large format printing materials are free from deference in the product of the produ	264 microns /10.4 mil per ISO 534 Test Method 98% per TAPPI T-425 Test Method 91% per TAPPI T-452 Test Method 130 per CIE Ganz 82 Test Method Matte 15 to 35° C / 59 to 95° F 20 to 80% RH 1+ years unlaminated, 2+ years laminated with Original HP 771 Vivid Photo Inks; 1+ with Original HP 91 Photo Inks; 1+ years unlaminated with Original HP 83 UV inks; 1- Original HP 70 Photo Inks on the HP Designjet Z5200 Postscript Printer and the HP I 200+ years away from direct sun with Original HP 771 Vivid Photo Inks, or Original Haway from direct sun with Original HP 83 UV inks ⁵ Water resistant with Original HP 771 Vivid Photo Inks or Original HP 91 Photo Inks ⁶ Instant dry (at 23° C, 50% RH) Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates 1 year, unopened in original packaging 0 to 40° C / 32 to 104° F 5 to 95% RH Recyclable through commonly available recycling programs Product of Switzerland Product numbers Roll sizes UPC codes Q6626B 610 mm x 30,5 m (24 in x 100 ft) 848412013573 Q6628B 1067 mm x 30,5 m (36 in x 100 ft) 848412013580 Q6630B 1524 mm x 30,5 m (60 in x 100 ft) 848412013597 HP large format printing materials are free from defects in materials and		

Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant-calculation assumes 6,000 Lux/12 hr day. For more information, see globalBMG.com/hp/t/printpermanence.

Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see globalBMG.com/hp/t/printpermanence.



For detailed information on the HP large format print media portfolio and to order, visit

globalBMG.com/hp

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



⁵ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.